



- Suggestions for Floor Foundation Preparation
1. Use gravel stones, to obtain a minimum soil bearing pressure of 1024lbs./ft<sup>2</sup> (49kPa)
  2. Use concrete with a minimum compressive strength of 2560PSI (17.7MPa) and tensile strength of 256PSI (1.8MPa)
  3. Take precautions so that there are no cracks in the concrete.
  4. Use a vibration isolator (such as asphalt) around the foundation base.
  5. To reinforce the concrete, lay steel bars (3/4in. dia., 19mm dia.) in the form of grid at a pitch of 5.91in. (150mm)
  6. Confirm that the inner walls of the foundation bolt pits are jagged, rough and uneven so as to facilitate the secondary poured concrete to adhere fast to the initially poured concrete.
  7. For the first step, pour the concrete with holes prepared for foundation bolts. After the concrete has been sufficiently cured, install the foundation bolts. Leveling blocks and other fittings and establish the rough level of the machine. For the second step, pour the concrete into the foundation bolt holes to secure the foundation bolts to the floor.
  8. When pouring the secondary concrete into the foundation bolt pits, fix the leveling blocks and the steel plates to the foundation bolts by tightening the set screw provided in the collar. After the concrete has been cured, level the machine and secure the leveling blocks to the machine by tightening the nuts (M16). At this time the collar is forced down onto the concrete along the foundation bolt and the tensile load is applied to bolt.
  9. Total volume of concrete 106.0ft<sup>3</sup> (3.0m<sup>3</sup>)
  10. It is advisable to mix a proper inflating agent (such as Denka CSA) in the concrete used to fill the anchor bolts pits so as to prevent the concrete from contracting after it has cured.
  11. Use a proprietary finish to the concrete surface to prevent water penetration and provide a smooth finish.
  12. This drawing is to be read in conjunction with the general arrangement drawing to ensure there is sufficient space around the machine for maintenance.

SPECIFICATION OF UNIT		THIRD ANGLE PROJECTION			
UNIT No.	CHK' D	DSGN	DRGNG	DRAWING	
5D5561004CO	031323	031323	031323	031323	
VC-E2 16X					
30T / H/WING CONVEYOR / ANCHOR BOLT		K.N	J.W	K.N	T-Y
		SCALE		NAME	
		1:12		VC-E2 16X	
		(1:6)		FOUNDATION DRAWING	
		DRAWING NO.		0 D55 FL C006 0	
QTY	DATE	DC NO.	SIGN		

Inch  
[ANCHOR BOLT]  
[mm]