




B-B SECTION



A DETAIL (S=1:3)
(4 PLACES)



B-B SECTION (S=1:3)
(5 PLACES)



B-B SECTION (S=1:3)
(5 PLACES)

- Suggestions for Floor Foundation Preparation
- 1) Use gravel stones to obtain a minimum soil bearing pressure of 49kPa (1024lbs/ft²).
 - 2) Use concrete with a minimum compressive strength of 17.7MPa (2560 PSI) and tensile strength of 1.98MPa (286 PSI).
 - 3) Take precautions so that there are no cracks in the concrete.
 - 4) 4 nos. whole anchors (marked #) should be positioned, drilled and set prior to set-up the machine.
 - 5) Use a vibration isolator (such as asphalt) around the foundation base.
 - 6) To reinforce the concrete, lay steel bars (19mm dia. 3/4in. dia.) in the form of grid at a pitch of 150mm (5.91in.).
 - 7) Total volume of concrete 1.9m³ (67.1ft³).
 - 8) Use a proprietary finish to the concrete surface to prevent water penetration and provide a smooth finish.
 - 9) This drawing to be read in conjunction with the general arrangement drawing to ensure there is sufficient space around the machine for maintenance.

THIS IS REDRAWN

SPECIFICATION OF UNIT		THIRD ANGLE PROJECTION			
UNIT No.	MASS PRODUCTION	APP'D	CHK'D	DSGN	DRAWING
5D6561003C2	AUGER/50T-MG/DRY PIT	121420	121420	121420	121420
		K.N	J.W	K.N	M.R.T
		SCALE	NAME		
		1:12	VC-Ez 20		
		FOUNDATION DRAWING			
		DRAWING NO.		0 D65 61 AC10 2	
QTY	DATE	DC NO.	SIGN		